

EFFECT OF DOUBLE STRATIFICATION ON BOUNDARY LAYER FLOW
AND HEAT TRANSFER OF NANOFLUID OVER A VERTICAL PLATE IN THE
PRESENCE OF CHEMICAL REACTION

LILY AFIZAH BINTI RAHAMAT

A project report submitted in partial
fulfilment of the requirement for the award of the
Degree of Master of Science (Applied Mathematics)

Fakulti Sains, Teknologi Dan Pembangunan Insan
Universiti Tun Hussein Onn Malaysia

JUNE 2015

This work is dedicated to my beloved parents

Rahamat bin Abd Jabar and Asmah binti Pukari

For their endless love, support, encouragement and blessing

I am honoured to have you as my parents

A special thanks to my loving husband

Md Ebrahim bin Tukiya

Who has been a great source of motivation and inspiration

For the deep support, undying love, trust and encouragement continues to surround

and support when this task looked like more than I could handle

You are my soulmate, my partner and my best friend who walks besides me in this
journey as a postgraduate student.

For my daughter

Nur Irdina Insyirah binti Md Ebrahim

You are my strength to finish all of this

Finally this report is dedicated to all those who believe in the richness of learning.

ACKNOWLEDGMENT

First of all, I am greatly indebted to ALLAH SWT on His blessing to make this project successful.

I would like to express my gratitude to honourable Prof. Dr. Ramasamy Kandasamy, my supervisor of Master's project for his guidance and support and unfailing patience throughout the course of this study. During the research, he helped me a lot especially in guiding to use Maple software. Then, during the discussion session, he tried to give me encouragement and assistance which finally leads me to the completion of this project.

Finally, I would like to dedicate my gratitude to the my parents, my lovely husband, my daughter, my siblings and my best friends who helped me directly or indirectly in the completion of this project. Their encouragement and guidance mean a lot to me. Their sharing and experience foster my belief in overcoming every obstacle encountered in this project. Thank you for giving me strength to chase my dreams.

Guidance, co-operation and encouragement from all people above are appreciated by me sincerely. Although I cannot repay the kindness from them, I would like to wish them to be well and happy always. Thank you for everything.

ABSTRAK

Masalah stratifikasi berganda ke atas aliran lapisan sempadan dan pemindahan haba teraruh kerana cecair nano di atas plat menegak dengan kehadiran tindak balas kimia disiasat. Nanopartikel mempunyai potensi yang besar untuk meningkatkan sifat-sifat pengangkutan haba berbanding dengan zarah konvensional cecair penggantungan, meter mili dan zarah bersaiz mikro meter. Persamaan pengangkutan yang digunakan dalam analisis termasuk kesan gerakan Brownian, parameter thermophoresis, nisbah parameter keapungan, parameter stratifikasi haba, parameter stratifikasi solutal dan parameter kadar tindak balas kimia. Persamaan pembezaan biasa bukan linear dan syarat sempadan yang berkaitan mereka pada mulanya diturunkan ke bentuk berdimensi oleh pembolehubah persamaan. Sistem yang mengakibatkan persamaan ini kemudiannya diselesaikan secara berangka dengan menggunakan perisian komputer algebra MAPLE 18. Perisian ini menggunakan perintah keempat kelima kaedah Runge Kutta Fehlberg sebagai kaedah untuk menyelesaikan masalah nilai sempadan secara berangka menggunakan arahan dsolve itu. Keputusan berangka yang diperolehi adalah halaju berdimensi, suhu berdimensi dan taburan kepekatan zarah berdimensi. Hasil daripada analisis didapati bahawa halaju berdimensi bendalir berkurangan dengan kenaikan parameter stratifikasi haba dan stratifikasi solutal. Keputusan berangka dibandingkan dan didapati bersetuju dengan keputusan yang diterbitkan sebelum ini pada kes-kes khas daripada masalah yang dikaji.

ABSTRACT

The problem of double stratification on boundary layer flow and heat transfer induced due to a nanofluid over a vertical plate in the presence of chemical reaction is investigated. Nanoparticles have a great potential to improve the thermal transport properties compared to conventional particles fluids suspensions, mili meter and micro meter sized particles. The transport equation which employed in the analysis including the effect of Brownian motion, thermophoresis parameter, buoyancy ratio parameter, thermal stratification parameter, solutal stratification parameter and chemical reaction rate parameter. The non-linear governing equations and their associated boundary conditions are initially cast into dimensionless forms by similarity variables. The resulting systems of equations are then solved numerically by using very robust computer algebra software MAPLE 18. This software uses a fourth-fifth order Runge Kutta Fehlberg method as a default to solve boundary values problems numerically using the dsolve command. Numerical results are obtained for dimensionless velocity, temperature and concentration distribution of particles. It is examined that the dimensionless velocity of the fluid decreases with the increases of thermal and solutal stratification parameter. The numerical results are compared and found to be in good agreement with the previous published result on special cases of the problem.

TABLE OF CONTENT

CONTENT

TABLE OF CONTENT	vii
LIST OF TABLE	x
LIST OF FIGURE	xii
LIST OF SYMBOL	xv
LIST OF APPENDIX	xviii

CHAPTER 1 INTRODUCTION

1.1	Background	1
1.2	Problem Statement	4
1.3	Objectives of study	4
1.4	Scopes of study	5
1.5	Organization of the thesis	5

CHAPTER 2 LITERATURE REVIEW

2.0	Nanoparticle	7
2.1	Nanofluid	8
2.2	Thermal Stratification	12
2.3	Double Stratification	13
2.4	Darcy's Law	13

2.5	Additional Form of Darcy's Law	17
2.5.1	Darcy's Law for Short Time Scales	17
2.5.2	Brinkman Form of Darcy's Law	17
2.5.3	Darcy-Forchheimer Law	18
2.5.4	Validity of Darcy's Law	18
2.6	Rayleigh Number	19
2.7	Reynolds Number	20
2.8	Chemical Reaction	22
2.9	Reaction Rate	24

CHAPTER 3 METHODOLOGY

3.1	Overview	26
3.2	Mathematical Formulation	27
3.3	Solution of The Problem	29
3.4	Numerical Solutions	41

CHAPTER 4 RESULT AND DISCUSSION

4.1	Overview	46
4.2	Effect Of Thermophoresis Parameter On Velocity, Temperature And Concentration Profiles	49
4.3	Effect Of Brownian Motion Parameter On Velocity, Temperature And Concentration Profile	52
4.4	Effect Of Bouyancy Ratio Parameter On Velocity, Temperature And Concentration Profile	55

4.5	Effect Of Thermal Stratification Parameter On Velocity, Temperature And Concentration Profile	58
4.6	Effect Of Solutal Stratification Parameter On Velocity, Temperature And Concentration Profile	61
4.7	Effect Of Distractive Chemical Reaction On Velocity, Temperature And Concentration Profile	65
4.8	Effect Of Generative Chemical Reaction On Velocity, Temperature And Concentration Profile	68

CHAPTER 5 CONCLUSIONS AND RECOMMENDATION

5.1	Conclusions	75
5.2	Recommendation	76

REFERENCES	77
-------------------	-----------

APPENDIX

Appendix A	81
Appendix B	82
Appendix C	95

LIST OF TABLE

3.1	Value of Set Parameter	43
3.2	Value of Distractive Chemical Reaction Parameter	44
3.3	Value of Generative Chemical Reaction Parameter	44
3.4	Value of Thermal Stratification Parameter	44
3.5	Value of Solutal stratification Parameter	44
3.6	Value of Brownian Motion Parameter	45
3.7	Value of Thermophoresis Parameter	45
3.8	Value of Buoyancy Ratio Parameter	45
4.1	Comparison Of Current Study Results And Previous Published Result	47
4.2	Velocity, Temperature And Concentration With $N_r=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	49
4.3	Velocity, Temperature And Concentration With $N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	52
4.4	Velocity, Temperature And Concentration With $N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	55
4.5	Velocity, Temperature And Concentration With $N_b=N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_2=0.5$, $\gamma=0.5$	58
4.6	Velocity, Temperature And Concentration With $N_b=N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=0.5$, $\gamma=0.5$	61
4.7	Velocity, Temperature And Concentration With $N_b=N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	65

4.8	Velocity, Temperature And Concentration With $Nb=Nr=Nt=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	68
4.9	Computed values of velocity $f'(0)$, temperature $\theta(0)$ and concentration $\phi(0)$ for different values of ϵ_1 and ϵ_2 when $Nb=Nr=Nt=0.5$, $Le=10$, $Pr=6.2$	71
4.10	Computed values of velocity $f'(0)$, temperature $\theta(0)$ and concentration $\phi(0)$ for different values of Nt , Nb and Nr when $Le=10$, $Pr=6.2$ $\epsilon_1=\epsilon_2=0.5$	73



LIST OF FIGURES

2.1	Diagram of water and nanofluid	10
2.2	Transmission Electron Microscope (TEM) Pictures of Nanofluids.	10
2.3	Diagram Showing Definitions and Direction for Darcy's Law	17
3.1	Flow Configuration and Coordinate System	27
4.1	Comparison of value velocity profile ϵ_1 with Fig. 2 of Wubshet Ibrahim and Makinde (2013)	48
4.2	Velocity graph for different values of ϵ_1 when $N_b=N_t=0.5$, $Le=10$, $Pr=1$, $\epsilon_2=0.5$ (Wubshet Ibrahim and Makinde, 2013)	49
4.3	Velocity graph for different values of N_t when $N_r=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0$.	49
4.4	Temperature graph for different values of N_t when $N_r=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	50
4.5	Concentration graph for different values of N_t when $N_r=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	50
4.6	Velocity graph for different values of N_b when $N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	52
4.7	Temperature graph for different values of N_b when $N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	53

4.8	Concentration graph for different values of N_b when $N_r=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	53
4.9	Velocity graph for different values of N_r when $N_t=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	55
4.10	Temperature graph for different values of N_r when $N_t=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	56
4.11	Concentration graph for different values of N_r when $N_t=N_b=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$, $\gamma=0.5$	56
4.12	Velocity graph for different values of ϵ_1 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_2=0.5$, $\gamma=0.5$	58
4.13	Temperature graph for different values of ϵ_1 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_2=0.5$, $\gamma=0.5$	59
4.14	Concentration graph for different values of ϵ_1 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_2=0.5$, $\gamma=0.5$	59
4.15	Velocity graph for different values of ϵ_2 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=0.5$, $\gamma=0.5$	62
4.16	Temperature graph for different values of ϵ_2 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=0.5$, $\gamma=0.5$	62
4.17	Concentration graph for different values of ϵ_2 when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=0.5$, $\gamma=0.5$	63
4.18	Velocity graph for different values of γ when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	65
4.19	Temperature graph for different values of γ when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	66
4.20	Concentration graph for different values of γ when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	66
4.21	Velocity graph for different values of γ when $N_r=N_b=N_t=0.5$, $Le=10$, $Pr=6.2$, $\epsilon_1=\epsilon_2=0.5$	68

- 4.22 Temperature graph for different values of γ when **69**
 $N_r = N_b = N_t = 0.5$, $Le = 10$, $Pr = 6.2$, $\epsilon_1 = \epsilon_2 = 0.5$
- 4.23 Concentration graph for different values of γ when **69**
 $N_r = N_b = N_t = 0.5$, $Le = 10$, $Pr = 6.2$, $\epsilon_1 = \epsilon_2 = 0.5$



LIST OF SYMBOLS

NOMENCLATURE

A	the cross-sectional area to flow
C_f	skin friction coefficient
$C_{\infty;0}$	ambient concentration
D_B	Brownian diffusion coefficient
D_T	thermophoresis diffusion coefficient
f	dimensionless stream function
h	dimensionless concentration function
k	thermal conductivity
κ	the intrinsic permeability of the medium
Le	Lewis number
Nb	Brownian motion parameter
Nr	buoyancy ratio parameter
Nt	thermophoresis parameter
Nu_x	local Nusselt number
Pr	Prandtl number
$(P_b - P_a)$	the total pressure drop
q	the flux

Ra_x	local Rayleigh number
Re	local Reynolds number
Sh_x	local Sherwood number
T	temperature of the fluid inside the boundary layer
$T_{\infty;0}$	ambient temperature
u, v	velocity component along x- and y-direction component along x- and y- direction



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

GREEK LETTERS

α	Thermal diffusivity
β	Volume expansion coefficient
η	Dimensionless similarity variable
μ	Dynamic viscosity of the fluid
ν	Kinematic viscosity of the fluid
ε_1	Thermal stratification
ε_2	Solutal stratification
$(\rho)_f$	Density of the fluid
$(\rho C)_f$	Heat capacity of the fluid
$(\rho C)_p$	Effective heat capacity of a nanoparticle
Ψ	Stream function
Φ_w	Nanoparticle volume fraction at the surface
Φ_∞	Nanoparticle volume fraction at large values of y
θ	Dimensionless temperature
τ	$\frac{(\rho C)_p}{(\rho C)_f}$
Υ	Chemical reaction rate
f'	Dimensionless velocity
ϕ	Dimensionless particle concentration

LIST OF APPENDIX

A	Gantt Chart for Project Master 1 and 2	81
B	Governing Equations	82
C	Maple Command For The Effect Of Thermal Stratification Parameter On Velocity, Temperature And Concentration Profile.	95



PTTA UTHM
PERPUSTAKAAN TUNKU TUN AMINAH

CHAPTER 1

1.1 BACKGROUND

Natural convection is a mechanism, or type of heat transport, in which the fluid motion is not generated by any external source (like a pump, fan, suction device, etc.) but only by density differences in the fluid occurring due to temperature gradients. In natural convection, fluid surrounding a heat source receives heat, becomes less dense and rises. The surrounding, cooler fluid then moves to replace it. This cooler fluid is then heated and the process continues, forming convection current; this process transfers heat energy from the bottom of the convection cell to top. The driving force for natural convection is buoyancy, a result of differences in fluid density. Natural convection has attracted a great deal of attention from researchers because of its presence both in nature and engineering applications and also their various engineering and industrial applications in heat transfer process.. In nature, convection cells formed from air rising above sunlight-warmed land or water are a major feature of all weather systems. Heat transfer by natural convection frequently occurs in many physical problems and engineering application such as geothermal systems, heat exchangers, chemical catalytic reactors, fiber and granular insulation, packed bed, petroleum reservoirs and nuclear waste repositories (Wubshet Ibrahim, 2013 and O.D.Makinde, 2013). Moreover, natural convection of heat and mass transfer occurs in many areas such as in the field of designing chemical processing equipment, distribution of temperature and moisture over agricultural fields and formation and dispersion of fog. In this system heat is transferred from a vertical plate to a fluid moving parallel to it by natural convection. This will occur in any system wherein the density of the moving fluid varies with position. These

phenomena will only be of significance when the moving fluid is minimally affected by forced convection.

Stratification of fluid arises due to temperature variations, concentration differences, or the presence of different fluids. In practical situations where the heat and mass transfer mechanisms run parallel, it is interesting to analyze the effect of double stratification (stratification of medium with respect to thermal and concentration fields) on the convective transport in micro polar fluid. The analysis of free convection in a doubly stratified medium is a fundamentally interesting and important problem because of its broad range of engineering applications. These applications include heat rejection into the environment such as lakes, rivers, and seas; thermal energy storage systems such as solar ponds; and heat transfer from thermal sources such as the condensers of power plants. The effect of stratification is an important aspect in heat and mass transfer and has been studied by several researches. In real-world situations where heat and mass transfer run simultaneously, it is significant to investigate the effect of double stratification on the convective transport by using nanofluid. A stratified fluid consisting of fluid parcels of various densities will tend under gravity to arrange itself so that the higher densities are found below lower densities. The vertical layering introduces an obvious gradient of properties in the vertical direction, which affects the velocity. Stratified fluids are universal in nature, present in almost any heterogeneous fluid body such that heterogeneous mixture in industries, salinity stratification in estuaries, density stratification of the atmosphere and many more example.

Analysis of thermal stratification is very important for solar engineering because higher energy efficiency can be achieved with better stratification and already shown by researchers that the thermal stratification in energy storage may significantly increase system performance. Chen and Eichorn, 1998, have been analyzed that natural convective flow over a heated vertical surface in a thermal stratified medium using the local non similarity method for the solution of the governing equations. The study is concerned with a natural convective flow of common fluids by the effects of double stratification on boundary layer flow and heat transfer of nanofluid over a vertical plate in the presence of chemical reaction because nowadays the natural convective flow and heat transfer using nanoparticle suspension in a base fluid has been active research area. The nanofluid is an advanced type of fluid containing nanometer sized particles (diameter less than

100nm) or fiber suspended in the ordinary fluid. Definitely the nanofluid are beneficial in the sense that the area more stable and have an acceptable viscosity and better wetting, spreading and dispersion properties on a solid surface. Nano fluids are used in different engineering application such as microfluidics, microelectronic, transportation, biomedical, solid state lighting and manufacturing. The research on heat transfer in nanofluid has been receiving increased attention worldwide.

Studies have been shown that a nanoparticle suspension in a base fluid curiously changes the transport property and heat transfer characteristic of a convectional base fluid. A uniform suspension of nanometer size solid particles and fiber in convectional base fluid is called nanofluid. Nano material is a new energy material since its particle size is the same as or smaller than the wavelength of de Broglie wave and coherent wave. Therefore, nanoparticle becomes too strongly absorb and selectively absorbs incident radiation. Based on the radiative motion properties of nanoparticle, the utilization of nanofluid in solar system becomes the new study hotspot. Scientist and engineers today are seeking to utilize solar radiation directly by converting it into useful heat or electricity.

Chemical reaction effects on heat and mass transfer are of considerable important in hydrometallurgical industries and chemical technology. In many chemical engineering processes, a chemical reaction occurs between a foreign mass and the fluid. A chemical reaction can be described as either a heterogeneous or homogeneous process, which depend on whether it occurs at an interface or as a single-phase volume reaction. Furthermore, research on combined heat and mass transfer with chemical reaction and thermophoresis effect can help in food processing, cooling towers, chemically reactive vapor deposition boundary layer in optical materials processing, catalytic combustion boundary layers, chemical diffusion in disk electrode modeling and carbon monoxide reactions in metallurgical mass transfer and kinetics. Several investigations have examined the effects of chemical reaction on the flow and heat and mass transfer past a vertical plate.

1.2 PROBLEM STATEMENTS

In this project, we will study numerically as well as physically the effect of double stratification on boundary layer flow and heat transfer of nanofluid over a vertical plate in the presence of chemical reaction. The effects of various governing parameters such as thermal stratification ε_1 , solutal stratification ε_2 , Brownian motion parameter N_b , thermophoresis parameter N_t , buoyancy ratio parameter N_r and chemical reaction γ on velocity $f'(\eta)$, temperature $\theta(\eta)$ and concentration $\phi(\eta)$ profiles will be examined. The coupled of ordinary differential equations for different values of governing parameters which are obtained by applying the fourth-fifth order Runge-Kutta Fehlberg method then will be solved numerically by using MAPLE software. Then the obtained result is compared to the previous result that has been done.

1.3 OBJECTIVES OF STUDY

The objectives of this thesis are:-

1. To analyze the effect of various governing parameters such as thermal stratification ε_1 , solutal stratification ε_2 , Brownian motion parameter N_b , thermophoresis parameter N_t , buoyancy ratio parameter N_r and chemical reaction γ on dimensionless velocity $f'(\eta)$, temperature $\theta(\eta)$ and concentration $\phi(\eta)$ profiles.
2. To compare the numerical result on special cases of the problem with previous published result.

1.4 SCOPE OF STUDY

This study is limited to the problem of effect of double stratification on boundary layer flow and heat transfer of nanofluid over a vertical plate in the presence of chemical reaction under some prescribed parameters effects. Some prescribed parameters, such as thermal stratification ε_1 , solutal stratification ε_2 , Brownian motion parameter N_b , thermophoresis parameter N_t , buoyancy ratio parameter N_r and chemical reaction γ on velocity $f'(\eta)$, temperature $\theta(\eta)$ and concentration $\phi(\eta)$ profiles.

The transport equations employed in this analysis which is including the effect of Brownian motion, thermophoresis, thermal stratification and solutal stratification; also the non-linear governing equations and their associated boundary conditions are initially cast into dimensionless forms by similarity variables. The set of equation are highly nonlinear coupled equations and cannot be solved analytically and numerical solution subject to the boundary condition. The set of equations are then obtained numerically by using the very robust computer algebra software Maple 18. This software uses a fourth –fifth order Runge Kutta Fehlberg method as default to solve boundary value problems numerically using the dsolve command.

1.5 ORGANIZATION OF THE THESIS

Chapter 1 provides some briefing on analysis background, its application in real world, some problem statement, objectives of the analysis, and scope of the study. Chapters 2 present a literature review about the nanoparticle, nanofluid, thermal stratification, solutal stratification, double stratification, Rayleigh number, Reynolds number, what is chemical reaction either distractive or generative reaction,

Chapter 3 presents the method that will be used along the analysis, how to reduces the governing equation to the dimensionless form, some surface introduction of calculation, some introduction of MAPLE 18 command. It also shows the equation that will use with MAPLE 18.

Chapter 4 presents the result and discussion on what finding that been obtain from the simulation, how the prescribe parameters effect on velocity, temperature and concentration profile. Chapter 5 presents the conclusion on the objectives that has been achieved. Some of recommendations for future work also mentioned in this chapter.



CHAPTER 2

LITERATURE REVIEW

2.0 NANOPARTICLE

Nanoparticles are particles between 1 and 100 nanometers in size. In nanotechnology, a particle is defined as a small object that behaves as a whole unit with respect to its transport and properties. Particles are further classified according to diameter. Ultrafine particles are the same as nanoparticles and between 1 and 100 nanometers in size. Coarse particles cover a range between 2,500 and 10,000 nanometers. Fine particles are sized between 100 and 2,500 nanometers. Nanoparticle research is currently an area of extreme scientific interest due to a wide variety of potential applications in biomedical, optical and electronic fields. Nanoparticles are of great scientific interest as they are, in effect, a bridge between bulk materials and atomic or molecular structures. A bulk material should have constant physical properties regardless of its size, but at the nano-scale size-dependent properties are often observed. Thus, the properties of materials change as their size approaches the nanoscale and as the percentage of atoms at the surface of a material becomes significant. For bulk materials larger than one micrometer (or micron), the percentage of atoms at the surface is insignificant in relation to the number of atoms in the bulk of the material.

REFEERENCES

- Buongiorno, J., et al., A benchmark study on the thermal conductivity of nanofluids. *Journal of Applied Physics*, 2009. 106(9):p.094312. View at Google Scholar.
- D.Srinivasacharya, Effect of double stratification on MHD free convection in a micropolar fluid, doi:10.1016/j.joems.2013.02.006 .View at Google Scholar.
- D. Srinivasacharya and G. Swamy Reddy, Chemical Reaction And Radiation Effects On Natural Convection In Porous Medium Saturated With Power-Law fluid. *Frontiers in Heat and Mass Transfer (FHMT)*, 3, 043008 (2012).
- D. Srinivasacharya and Ch. Ram Reddy, Effect of Double Stratification on Mixed Convection in a Micropolar Fluid. *MATEMATIKA*, 2012, Volume 28, Number 2, 133–149
- Elena V. Timofeeva, Wenhua Yu, David M. France, Dileep Singh, Jules L. Routbort, *Nanofluids for Heat Transfer: An Engineering Approach*, October 2010
- Etherington, H., ed. *Nuclear Engineering Handbook*. 1958, McGraw – Hill Book Company, Inc.: New York, USA. View at Google Scholar
- Hamilton, R.L. and O.K. Crosser, Thermal conductivity of heterogeneous two-component systems. *Industrial & Engineering Chemistry Fundamentals*, 1962. 1(3): p. 187-191. View at Google Scholar
- http://www.ehow.com/info_8730508_define-thermal-stratification.html
- Ibrahim, Wubshet, and O. D. Makinde. "The effect of double stratification on boundary- layer flow and heat transfer of nanofluid over a vertical plate. " *Computers & Fluids* 86 (2013): 433-441.

- K.-F. V. Wong and T. Kurma, "Transport properties of alumina nanofluids," *Nanotechnology*, vol. 19, no. 34, Article ID 345702, 8 pages, 2008. View at Publisher View at Google Scholar
- Kabelac, S. and J.F. Kuhnke, Heat transfer mechanisms in nanofluids –experiments and theory--. *Annals of the Assembly for International Heat Transfer Conference*, 2006. 13:p. KN-11. View at Google Scholar
- Kakaç, Sadik; Anchasa Pramuanjaroenkij (2009). "Review of convective heat transfer enhancement with nanofluids". *International Journal of Heat and Mass Transfer (Elsevier)* 52: 3187–3196.
- Kaufui V. Wong and Omar De Leon *Applications of Nanofluids: Current and Future*, *Advances in Mechanical Engineering Volume 2010* (2010), Article ID 519659, 11 pages
- K. Kaladhara, D. Srinivasacharya, Effects Of Thermal And Solutal Stratification On Mixed Convection Flow Along A Vertical Plate Saturated With Couple Stress Fluid. *Frontiers in Heat and Mass Transfer (FHMT)*, 5, 11 (2014)
- Kuznetsov AV, Nield DA, Natural convective boundary layer flow of a nanofluid past a vertical plate, *Int J Therm Sci* 2010;49:243-7.
- Kuznetsov, A.V.; Nield, D.A. "Natural convective boundary-layer flow of a nanofluid past a vertical plate". *International Journal of Thermal Sciences* 49 (2): 243–247.
- Maxwell, J.C., *A Treatise on Electricity and Magnetism*. 1873, Oxford, UK: Clarendon. View at Google Scholar
- M.Q. Al-Odat and T.A. Al-Azab, Influence of Chemical Reaction on Transient Mhd Free Convection Over A Moving Vertical Plate. *Emirates Journal for Engineering Research*, 12 (3), 15-21 (2007)
- Minkowycz, W., et al., *Nanoparticle Heat Transfer and Fluid Flow*, CRC Press, Taylor & Francis, 2013

Prasher, R., et al., Measurements of nanofluid viscosity and its implications for thermal applications. *Applied Physics Letters*, 2006. 89(13): p. 133108-133110. View at Google Scholar

P. R. Sharma, Navin Kumar and Pooja Sharma, Influence of Chemical Reaction and Radiation on Unsteady MHD Free Convective Flow and Mass Transfer through Viscous Incompressible Fluid Past a Heated Vertical Plate Immersed in Porous Medium in the Presence of Heat Source. *Applied Mathematical Sciences*, Vol. 5, 2011, no. 46, 2249 – 2260.

R. Kandasamy, K. Periasamy, K.K. Sivagnana Prabhu , Chemical reaction, heat and mass transfer on MHD flow over a vertical stretching surface with heat source and thermal stratification effects. *International Journal of Heat and Mass Transfer* 48 (2005) 4557–4561

Srinivasacharya Darbhashayanam and Upendar Mendu, Thermal radiation and chemical reaction effects on magnetohydrodynamic free convection heat and mass transfer in a micropolar fluid. *Turkish Journal of Engineering & Environmental Sciences* 2014.

S. U. S. Choi, “Nanofluids: from vision to reality through research,” *Journal of Heat Transfer*, vol. 131, no. 3, pp. 1–9, 2009.

Stephen U. S. Choi, Nanofluids: From Vision to Reality Through Research , *J. Heat Transfer* 131(3), 033106 (Jan 21, 2009) (9 pages)

Trisaksri, V. and S. Wongwises, Critical review of heat transfer characteristics of nanofluids. *Renewable & Sustainable Energy Reviews*, 2007. 11(3): p. 512-523. View at Google Scholar

Wikipedia, the free encyclopedia, Darcy’s Law

Wikipedia, the free encyclopedia, Nanoparticle

Yu, W., et al., Review and comparison of nanofluid thermal conductivity and heat transfer enhancements. *Heat Transfer Engineering*, 2008. 29(5): p. 432-460. View at Google Scholar

Yu, W., et al., Thermophysical property-related comparison criteria for nanofluid heat transfer enhancement in turbulent flow. Applied Physics Letters, 2010. 96: p. 213109-3. View at Google Scholar

Zheng Wen Zeng and Reid Grigga, 2005, Criterion for Non-Darcy Flow in Porous Media

